

# SNOH-LED

Type:	
Job Name:	

### Construction:

- Aluminum Chassis
- Diffuser is extruded white smooth acrylic

### Light Source:

- LED
- Dimming to 10% **Included**

### Notes:

- Canopy mounts to standard "J-Box"
- Custom mounting heights available
- Single ridge 15 degree swivel stem standard (1S15)
- Standard 24" stem length, consult factory for custom lengths.
- Bottom of fixture is open
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components



### SNOH -11

Stem length - 24"

*\* Overall Height equals stem length + fixture height*

Diameter - 6"



## ORDERING INFORMATION

**Example: SNOH-11-LED-F3B-4-T6-WSA-1S15-35"OAH**

### SNOH-11-LED

Size	LED					Kelvin	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star				
11-LED	F3B	18	1770	0-10v	NO	2 3000K 3 3500K 4 4000K	<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige  <b>Optional</b> (See Price List) <b>M17</b> Brass Powder <b>M16</b> Antique Brass	WSA White Smooth Acrylic	<b>(Suspension Systems)</b> Please list <b>Over All Height</b> <b>1S15</b> - Single 15° Swivel Stem (Standard) <b>1SLM45</b> - Single Stem 45 degree swivel <b>WSJ</b> - White "SJ" Cord <b>BSJ</b> - Black "SJ" Cord <b>1AC</b> - Single Aircraft Cable  <b>DIM</b> LED dimming driver (0 - 10v)
	1E26								



28435 Industry Drive., Valencia, California 91355  
 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 www.lightwayind.com • sales@lightwayind.com

