

SRLW-LED

Construction:

- Aluminum housing and chassis
- Diffuser is white textured or optional white smooth polycarbonate.
- Optional alabaster lenses

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Keyhole slots right and left
- Custom cage styles available
- Optional photocell (option 21) – specify voltage
- Optional battery backup
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



SRLW-10-LED

Height - 10"
Width - 11"
Depth - 6"

SRLW-14-LED

Height - 14"
Width - 18"
Depth - 8"



ORDERING INFORMATION

Example: SRLW-14-LED-F1P-4-B1-WTP

SRLW

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options
10-LED	F1H	9	1400	0-10v	YES	2 3000K 4 4000K Optional 3 3500K		B1 Satin Black	WTP White Textured Polycarbonate Optional Lens Material (See Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components 90CRI Consult Factory 16 Bottom Lens 21 Photocell - See Notes -01 120 volt -02 277 volt Battery Backup Options (SRLW-14 only) (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
	F1O	10	1065	TRIAC/ELV	YES			B2 Text Black		
	F1P	15	1724	TRIAC/ELV	YES			Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White		
	F1J	20	2820	0-10v	YES			T4 Shimmer Gray		
14-LED	F1H	9	1400	0-10v	YES			M13 Anod Silver		
	F1O	10	1065	TRIAC/ELV	YES			T6 Pewter		
	F1P	15	1724	TRIAC/ELV	YES			W13 Pearl Beige		
	F1J	20	2820	0-10v	YES			Optional (See Price List) M17 Brass Powder M16 Antique Brass		



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

