

# PLVH-LED

## Construction:

- Steel housing and chassis
- Bowl is frosted smooth glass
- Optional white smooth acrylic or alabaster acrylic bowl

## Light Source:

- LED
- Dimming to 10% **Included**


## Notes:

- Canopy mounts to J-Box with integral safety cable
- Tri-Pod with hub and chain is standard
- Custom mounting heights available
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



	PLVH-17	PLVH-21
A	5"	7"
B	19 1/2"	19 1/2"
C	16 1/2"	16 1/2"
OAH	41"	47"
D	16 1/2"	20 1/2"



## ORDERING INFORMATION

Example: PLVH-21-LED-F1Q-4-T6-FSG-DIM

### PLVH

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
17-LED		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige  Optional (See Price List) <b>M17</b> Brass Powder	<b>FSG</b> Frosted Smooth Glass  Optional Lens Material (see Price List)	<b>DIM</b> LED dimming driver (0 - 10v) <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v See Resource Page  <b>ES</b> Energy Star listed components <b>90CRI</b> Consult Factory  <b>OCCHFA</b> Concealed Occupancy Sensor See Sensor Resource Sheet  Optional Voltage <b>-347V</b> Input voltage to 347v  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes
	F1L	9	1400	0-10v	YES	Optional 3 3500				
	F1K	13	2115	0-10v	YES					
	O3B	22	3000	0-10v	NO					
	L1A	36	4000	0-10v	NO					
	F1P	15	1361	TRIAC/ELV	YES					
F1Q	23	2057	TRIAC/ELV	YES						
21-LED	F1K	13	2115	0-10v	YES					
	L1A	36	4000	0-10v	NO					
	F1P	15	1361	TRIAC/ELV	YES					
	F1Q	23	2057	TRIAC/ELV	YES					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

