

PCLC-LED

Construction:

- Steel pan and rings
- Diffuser is white smooth acrylic
- Optional high efficiency white smooth acrylic lens designed for LED light source (WSAHE)

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- Optional battery backup - Requires 1 3/4" extension ring
- Ceiling or Wall Mount
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

| | |
|-----------|--|
| Type: | |
| Job Name: | |



| | | |
|--|--|--|
| PCLC-12 Height - 3" w/ext ring - 5 1/4" Diameter - 12" | PCLC-15 Height - 3" w/ext ring - 5 1/4" Diameter - 15" | PCLC-21 Height - 3 3/8" w/ext ring - 5 1/4" Diameter - 21 1/4" |
|--|--|--|



ORDERING INFORMATION

Example: PCLC-15-LED-2R-F1P-4-T6-WSA-DIM

| Size | LED | | | | | Kelvin | Finish | Diffuser | Options |
|-----------------------|------------|-------|---------------|-----------|-------------|---|--|---|---|
| | | Watts | Source Lumens | Dimming | Energy Star | | | | |
| PCLC-12-2R-LED | F1L | 9 | 1400 | 0-10v | YES | 2 3000K 4 4000K Optional 3 3500K | T6 Pewter W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (see Price List) W1 Yolk W3 Text White B1 Satin Black B2 Text Black T4 Shimmer Gray M13 Anod Silver W13 Pearl Beige | WSA White Smooth Acrylic Optional Lens Material (see Price List) WSAHE White Smooth Acrylic High Efficiency | DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components T24 Title 24/JA8 Compliant (F10, F1P & F1Q configuration only) 90CRI Consult Factory OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet Battery Backup Options (Requires 1 3/4" extension ring) (Available with 0-10v only) PCLC-15 and 21 only BB10 10 Watts (1170lm) for 90-Minutes |
| | F1O | 10 | 863 | TRIAC/ELV | YES | | | | |
| | F1P | 15 | 1361 | TRIAC/ELV | YES | | | | |
| PCLC-15-2R-LED | F1K | 13 | 2115 | 0-10v | YES | | | | |
| | F1P | 15 | 1361 | TRIAC/ELV | YES | | | | |
| | F1Q | 23 | 2057 | TRIAC/ELV | YES | | | | |
| PCLC-21-2R-LED | L1A | 36 | 4000 | 0-10v | NO | | | | |



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

