

PDLH-LED

Construction:

- Steel housing and chassis
- Bottom lens is white frosted acrylic
- Field adjustable aircraft cable

Light Source:

- LED
- Dimming to 10% **Included**


Notes:

- Mounts to standard junction box
- UL and CUL listed **DAMP** location
- Optional battery backup
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



	PDLH-24	PDLH-36	PDLH-47
A	24"	36"	47"
B	3"	3"	3"
C	2 1/2"	2 1/2"	2 1/2"
D	12"	24"	35"
OAH	6 - 24"	6 - 24"	6 - 24"



ORDERING INFORMATION

Example: **PDLH-36-LED-O3C-4-T4-WSA**

PDLH

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Suspension/Options
24-LED	O2C	18	2420	0-10v	NO	2 3000K 3 3500K 4 4000K I		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel	WFA White Frosted Acrylic	(Suspension Systems) 2AC__ - Aircraft Cable w/ WSJ - White "SJ" Cord BSJ - Black "SJ" Cord GSJ - Gray "SJ" Cord DIM LED dimming driver (0 - 10v) Battery Backup Options Available in 36" and 47" only BB08 Battery backup unit providing 8 Watts (1080lm) for 90-Minute
36-LED	O3C	27	3630	0-10v	NO					
47-LED	O4C	36	4840	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

