

SOLP-LED

Construction:

- Steel housing and chassis
- Diffuser is white textured polycarbonate
- Optional alabaster acrylic lenses

Light Source:

- LED

Notes:

- Mounts to 3" round pole – fitter included
- Fixture dimensions excluded fitter
- See supplemental spec sheet on website for pole options
- UL and CUL listed **WET** location
- LED Components
 - OReplaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

| | |
|------------------|--|
| Type: | |
| Job Name: | |



SOLP-15-LED

Height - 15"
Width - 8 1/4"
Depth - 8 1/4"

SPLP-22

Height - 22"
Width - 12"
Depth - 12"



ORDERING INFORMATION

Example: SOLP-15-LED-O4B-4-Z1-WTP

SOLP

| Size | LED | | | | | Kelvin | Finish | Diffuser | Options | | | | | | |
|---------------|-------------|-------|---------------|-----------|-------------|----------------------------|---|---|--|--|--|--|--|--|--|
| | | Watts | Source Lumens | Dimming | Energy Star | 2 3000K 4 4000K | B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass | WTP White Textured Polycarbonate Optional Lens Material (See Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster | Optional Voltage -347V Input voltage to 347v Pole Options (see supplemental spec sheet on website and price list) | | | | | | |
| 15-LED | 1E26 | | 0 | TRIAC/ELV | NO | Optional 3 3500K | | | | | | | | | |
| | O4B | 29 | 4000 | 0-10v | NO | | | | | | | | | | |
| | O4C | 36 | 4840 | 0-10v | NO | | | | | | | | | | |
| 22-LED | O4C | 36 | 4840 | 0-10v | NO | | | | | | | | | | |
| | O8C | 72 | 9680 | 0-10v | NO | | | | | | | | | | |



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

