

# ABUC-LED

## Construction:

- Steel Pan
- Steel spun trim ring
- Diffuser is white smooth acrylic

## Light Source:

- LED
- Dimming to 10% **Included**
- Replaceable LED Engine

## Notes:

- Keyhole slots for standard J-box
- Brushed Nickel finish (standard)
- Cast upright accent
- Wall or ceiling mount
- Fastenerless appearance
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



### ABUC-14-LED

Height - 5 5/8"  
Diameter - 14"



## ORDERING INFORMATION

Example: ABUC-14-LED-F1P-4-P9-WSA

### ABUC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
14-LED	F1L	9	1400	0-10v	YES	2 3000K 4 4000K  Optional 3 3500K	P9 Brushed Nickel  Optional (See Price List)  B1 Satin Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk W2 Gloss White W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page  ES Energy Star listed components T24 Title 24/JA8 Compliant (F10 & F1P configuration only) 90CRI Consult Factory  OCCHFA Integrated Sensors See Sensor Resource Sheet  Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes	
	F1O	10	863	TRIAC/ELV	YES					
	F1P	15	1361	TRIAC/ELV	YES					
	F1K	13	2115	0-10v	YES					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

