

RHCH-LED

Construction:

- Steel housing and chassis
- Diffuser is .125" thick white smooth acrylic
- Optional alabaster acrylic is .125" thick

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Canopy mounts to J-Box with integral safety cable
- Custom mounting heights available
- Single stem suspension with 45-degree swivel
- Optional battery backup
- Optional bottom lens is white smooth acrylic
- Down Light - Consult Factory
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



RHCH-22

Height - 22"
Width - 10"
OAH - 44"

RHCH-30

Height - 30"
Width - 10"
OAH - 60"



ORDERING INFORMATION

Example: RHCH-22-LED-O7C-4-Z1-BAA-OAH44

RHCH

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 York White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster Optional Bottom Lens (see Price List) WBL White Bottom Lens	(Suspension Systems) Please list Over All Height 1S45 - Single Stem (Standard) 1SLM45 - Single Stem 45 degree swivel 1S154AC - Single Stem w/Aircraft Cable 4AC - Aircraft Cable w/SJ cord WSJ - White "SJ" Cord BSJ - Black "SJ" Cord DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page 90CRI Consult Factory Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
22-LED	O7C	63	8470	0-10v	NO	Optional 3 3500K		Optional (See Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel		
30-LED	O8C	72	9680	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

