

PLPH-LED

Construction:

- Steel pan and rings
- Diffuser is white smooth acrylic
- Optional high efficiency white smooth acrylic lens designed for LED light source (WSAHE)

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Canopy mounts to standard J-Box
- Custom stem heights available
- No uplight
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



PLPH-21

Height - 4 3/8"

Diameter - 21"

Overall Height - 25"



ORDERING INFORMATION

Example: PLPH-21-LED-L1A-4-T6-WSAHE

PLPH

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory
21-LED	L1A	36	4000	0-10v	NO	Optional 3 3500		Optional Lens Material (see Price List) WSAHE White Smooth Acrylic High Efficiency		90CRI Consult Factory OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet
								Optional (See Price List) M17 Brass Powder		



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

