

PDSW-LED

Construction:

- Aluminum housing and chassis
- Bottom lens is white frosted or clear smooth acrylic, or optional clear prismatic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware include
- Optional J-Box with knockouts for surface conduit (39)
- Dark sky compliant
- ADA Compliant
- Optional Battery Backup increases depth to 4"
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



PDSW-5-LED

Height - 5 1/8"
Width - 7 1/8"
Depth - 3 1/2"

PDSW-12-LED

Height - 5 1/8"
Width - 12"
Depth - 3 1/2"



ORDERING INFORMATION

Example: PDSW-5-LED-01A-4-B1-CPA

PDSW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
5-LED	01A	6	800	0-10v	NO	2 3000K 3 3500K 4 4000K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Gold Brass P2 Brushed Alum P9 Brushed Nickel	WFA White Frosted Acrylic CSA Clear Smooth Acrylic Optional Lens Material (See Price List) CPA Clear Prismatic Acrylic	DIM LED dimming driver (0 - 10v) 21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt 39 J-Box with Knockouts (increases depth by 1 1/4") * UP/DN "Damp listing only" (Up/Down Light) Battery Backup Options (Increases fixture depth to 4") BB10 10 Watts (1170lm) for 90-Minutes	
	01M	15	2050	0-10v	NO					
12-LED	01C	9	1210	0-10v	NO					
	02C	18	2420	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

