

# THOW-LED

## Construction:

- Steel housing and chassis
- Diffuser is .10" thick extruded white acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Center lockup - hardware included
- Open top and bottom
- Horizontal or vertical mounting
- Optional battery backup
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components
- **For WET listed version see MANW Series**

Type:	
Job Name:	



### THOW-16-LED

Height - 16"  
Width - 7 1/8"  
Depth - 4"

### THOW-24-LED

Height - 24"  
Width - 7 1/8"  
Depth - 4"



## ORDERING INFORMATION

Example: THOW-16-LED-O2C-4-B1-WSA

### THOW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
16-LED	O2C	18	2420	0-10v	NO	2 3000K 4 4000K			WSA White Smooth Acrylic	<b>DIM</b> LED dimming driver (0 - 10v) <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v Consult Factory  <b>90CRI</b> Consult Factory  Optional Voltage <b>-347V</b> Input voltage to 347v  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes
24-LED	O2C	18	2420	0-10v	NO					
						Optional 3 3500K				

\* Interior Use Only



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

