

MEOW-LED

Construction:


- Steel Housing and chassis
- Diffuser UV-stabilized, high impact resistant, DR acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; Hardware include
- Mounts on a Standard J-Box
- Lens on all five sides
- Optional battery backup available on fixtures 526 & larger
- Optional photocell (21) increases fixture depth 1/2"
- UL and CUL listed **WET** location
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



	DIM 'A'	Mount-Center
MEOW-513	13"	6.5"
MEOW-518	18"	9"
MEOW-526	26"	13"
MEOW-538	38"	19"
MEOW-550	50"	25"

Type:	
Job Name:	



ORDERING INFORMATION

Example: MEOW-526-LED-O2C-3-Z3-WSA

MEOW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K				
513-LED	O1C	9	1210	0-10v	NO			WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)	
518-LED	O2A	12	1600	0-10v	NO				21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt	
526-LED	O2C	18	2420	0-10v	NO				42 All Aluminum Construction	
538-LED	O3C	27	3630	0-10v	NO					
550-LED	O4C	36	4840	0-10v	NO					
									Battery Backup Options (MEOW-526 and Larger only) BB10 10 Watts (1170lm) for 90-Minutes	



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

