

PCMC-LED

Construction:

- Steel housing
- Diffuser is frosted smooth glass

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup with keyhole slots – hardware included
- UL and CUL listed DAMP location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Dimming (10% or 1%)
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



PCMC-15
 Height - 5"
 Diameter - 14 1/2"



ORDERING INFORMATION

Example: PCMC-15-LED-F1K-4-W2-FSG

PCMC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
15-LED	F1L	9	1400	0-10v	YES	2 3000K 4 4000K Optional 3 3500	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder	FSG Frosted Smooth Glass	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components 90CRI Consult Factory 42 Aluminum Pan Optional Voltage -347V Input voltage to 347v	
	F1O	10	863	TRIAC/ELV	YES					
	F1K	13	2115	0-10v	YES					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

