

ALUW-LED

Construction:

- Steel housing and chassis
- Extruded aluminum cover
- Diffuser is .125" thick formed white smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts to standard J-Box with anchor holes top and bottom
- Horizontal or vertical mounting
- ADA compliant
- Optimal battery backup
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Dimming (10% or 1%)
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



ALUW-24	ALUW-36	ALUW-48
Height - 23"	Height - 34 3/4"	Height - 46 3/4"
Depth - 3 3/4"	Depth - 3 3/4"	Depth - 3 3/4"
Width - 6 1/4"	Width - 6 1/4"	Width - 6 1/4"
MC - 12 1/2"	MC - 17 3/8"	MC - 23 3/8"



ORDERING INFORMATION

Example: ALUW-36-LED-O3C-4-T6-WSA

ALUW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
24-LED	O2B	15	2000	0-10v	NO	2 3000K 4 4000K	B1 Satin Black T6 Pewter Z3 Text Bronze	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory 90CRI Consult Factory Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes	
36-LED	O3C	27	3630	0-10v	NO	Optional 3 3500K	Optional Finishes (see Price List) M13 Anod Silver T4 Shimmer Gray W13 Pearl Beige P9 Brushed Nickel M16 Antique Brass			
48-LED	O4C	36	4840	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

