

PLPC-LED

Type:	
Job Name:	

Construction:

- Steel pan and rings
- Diffuser is white smooth acrylic
- Optional high efficiency white smooth acrylic lens designed for LED light source (WSAHE)

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- Optional battery backup - Requires 1 3/4" extension ring
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



PLPC-12-LED

Height - 3 1/4"
w/ext ring - 5 1/4"
Diameter - 12"

PLPC-15-LED

Height - 3 1/4"
w/ext ring - 5 1/4"
Diameter - 15"

PLPC-21-LED

Height - 4 3/8"
w/ext ring - 5 1/4"
Diameter - 21 1/4"



ORDERING INFORMATION

Example: PLPC-15-LED-F1K-4-T6-WSA

PLPC

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options
12-LED	F1L	9	1400	0-10v	YES	2 3000K 4 4000K Optional 3 3500K		T6 Pewter	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
	F1O	10	863	TRIAC/ELV	YES			W2 Gloss White		
	F1P	15	1361	TRIAC/ELV	YES			Z1 Satin Bronze Z3 Text Bronze Optional (see Price List)		
15-LED	F1K	13	2115	0-10v	YES			W1 Yolk	Optional Lens Material (see Price List) WSAHE White Smooth Acrylic High Efficiency	ES Energy Star listed components T24 Title 24/JA8 Compliant (F1O, F1P & F1Q configuration only)
	F1P	15	1361	TRIAC/ELV	YES			W3 Text White		
	F1Q	23	2057	TRIAC/ELV	YES			B1 Satin Black B2 Text Black		
	F1R	28	4015	0-10v	YES			T4 Shimmer Gray		
21-LED	L1A	36	4000	0-10v	NO			M13 Anod Silver W13 Pearl Beige		90CRI Consult Factory OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet Battery Backup Options (Requires 1 3/4" extension ring) (Available with 0-10v only) PLPC-15 and 21 only BB10 10 Watts (1170lm) for 90-Minutes

28435 Industry Drive., Valencia, California 91355

West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201

East Coast Sales: 866-350-0991 • fax 866-490-5754

www.lightwayind.com • sales@lightwayind.com

