

# DXEW-LED

## Construction:

- Steel housing and chassis
- Clear prismatic polycarbonate lens behind shield

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Integral mounting plate; keyhole slots left and right
- Optional knockouts (KO) top and bottom
- Optional photocell - option 21 (specify voltage)
- Optional battery backup
- UL and CUL listed **WET** location
- LED Components
  - CRI > 80
  - Dimming (10% or 1%)
  - 120/277 volt driver
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



### DXEW-14

Height - 14"  
Width - 22"  
Depth - 11"



## ORDERING INFORMATION

Example: DXEW-14-LED-O2A-2-W2

### DXEW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
14-LED	O2A	12	1600	0-10v	NO	2 3000K 4 4000K		B1 Satin Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W2 Gloss White W1 Yolk White Z1 Satin Bronze Z3 Text Bronze		DIM LED dimming driver (0 - 10v) Dimming to 10% <b>(Included)</b>
	O4A	24	3200	0-10v	NO	Optional 3 3500K		Optional Finishes (see Price List) M17 Brass Powder		42 All Aluminum Construction 21 Photocell - See Notes -01 120 volt -02 277 volt  KO Knockouts (See Notes)  Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355  
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
East Coast Sales: 866-350-0991 • fax 866-490-5754  
www.lightwayind.com • sales@lightwayind.com

