

NEFW-LED

Construction:

- Housing and chassis is steel
- Diffuser is vandal resistant acrylic


Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; Hardware include
- Mounts on a 2x4 jbox or 4" square post
- Optional two color choice of the frame and cover
- Optional battery backup available on fixtures 426 & larger
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



	DIM 'A'	Mount-Center
NEFW-413	13"	6.5"
NEFW-426	26"	13"
NEFW-438	38"	19"
NEFW-450	50"	25"
NEFW-460	60"	30"



ORDERING INFORMATION

Example: NEFW-438-LED-O3C-3-Z3-Z3-DIM

NEFW

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Front Deco Finish	Options
413-LED	O1C	9	1210	0-10v	NO	2 3000K 3 3500K 4 4000K		B1 Satin Black	B1 Satin Black	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) 42 All Aluminum Construction Battery Backup Options Available (426 & Larger) BB10 Battery backup unit providing 10 Watts (1170lm) for 90-Minute
426-LED	O2C	18	2420	0-10v	NO			B2 Text Black	B2 Text Black	
438-LED	O3C	27	3630	0-10v	NO			Z1 Satin Bronze	Z1 Satin Bronze	
450-LED	O4C	36	4840	0-10v	NO			Z3 Text Bronze	Z3 Text Bronze	
460-LED	O5C	45	6050	0-10v	NO			W1 Yolk White	W1 Yolk White	
								W2 Gloss White	W2 Gloss White	
								T4 Shimmer Gray	T4 Shimmer Gray	
								M13 Anod Silver	M13 Anod Silver	
								T6 Pewter	T6 Pewter	
								W13 Pearl Beige	W13 Pearl Beige	
								Optional (See Price List)	Optional (See Price List)	
								M16 Antique Brass	M16 Antique Brass	
								P2 Brushed Alum	P2 Brushed Alum	
								P9 Brushed Nickel	P9 Brushed Nickel	



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

