

WSGW-LED

Construction:

- Cast aluminum housing and frame
- White steel pan reflector
- White smooth polycarbonate lens

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Surface mounts to 4" outlet box
- Vandal Resistant
- Recommended mounting heights 8 - 20 feet
- Optional Photocell (specify voltage)
- Optional Microwave Sensor
- Optional Battery Backup
- CSA listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components


Type:	
Job Name:	



WSHW



WSRW



WSGW-12

Length - 12 1/2"

Width - 12 1/2"

Depth - 4 1/4"



ORDERING INFORMATION

Example: WSGW-12-LED-S1C-4-W99-WSP

WSGW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Deliver Lumens	Dimming	Energy Star					
12-LED	S1C	17	1980	0-10v	NO	2 3000K 4 4000K 5 5000K		W99 White Z99 Bronze	WSP White Smooth Polycarbonate	DIM LED dimming driver (0 - 10v) 21 Photocell - See Notes -01 120 volt -02 277 volt OCCHFA Concealed Occupancy Sensor (120-277V only) Optional Voltage -347V Input voltage to 347v Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

