

BCRP-LED

Construction:

- Cast aluminum pole fitter
- Globe is clear textured acrylic or polycarbonate

Light Source:

- LED

Notes:

- Mounts to 3" round pole – cast aluminum fitter included
- Fixture dimensions include fitter
- Globe is available in Type III or V light pattern
- See spec sheet on website for pole options
- EPA rating of 2.1
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



shown with spike finial



BCRP-34

Height - 32 1/4"

Width - 16"

Depth - 16"

Finial Add 2"



WALL MOUNT OPTION

ORDERING INFORMATION

Example: BCRP-34-LED-O4C-4-B99-CTP-T5-SF

BCRP

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		B99 Black	CTA Clear Textured Acrylic	27 Wall Mount Bracket
34-LED	O4C	36	4840	0-10v	NO				Optional Globe (See price list)	NR Neck Ring
	F4E	58	9388	DIM or DIMLD	NO			CTP Clear Textured Polycarbonate		FF Flame Finial
	1E26		0	TRIAC/ELV	NO			Light Pattern T3 Type III T5 Type V		SF Spike Finial
										Pole Options (see supplemental spec sheet on website and price list)



28435 Industry Drive., Valencia, California 91355
 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 www.lightwayind.com • sales@lightwayind.com

