

# MFRW-LED

## Construction:

- Steel housing and chassis
- Diffuser is .10 extruded white acrylic


## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Keyhole slots left and right
- Top and bottom white acrylic lens - standard
- Optional photocell (21) increases fixture depth 1 ½"
- Optional battery backup
- Optional lens cover (NCL) prevents up/down light
- UL and CUL listed **WET** location
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components
- You may also like the [MERW](#) or [MENW](#) Series

Type:	
Job Name:	



### MFRW-926

- (A) Height - 26"
- (B) Width - 9"
- (C) Depth - 5 ½"

### MFRW-1126

- (A) Height - 26"
- (B) Width - 11 ¼"
- (C) Depth - 6 ½"



## ORDERING INFORMATION

Example: MFRW-926-LED-O2C-3-Z1-WSA

### MFRW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
926-LED	O2C	18	2420	0-10v	NO	2 3000K 3 3500K 4 4000K		<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>W3</b> Text White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter  <b>Optional</b> (See Price List) <b>M17</b> Brass Powder	WSA White Smooth Acrylic	<b>DIM</b> LED dimming driver (0 - 10v)  <b>Z1</b> Photocell - Specify voltage 01 - 120 volt 02 - 277 volt  <b>NCL</b> Aluminum Lens Cover - See Notes  Optional Voltage <b>-347V</b> Input voltage to 347v  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes
	O4C	36	4840	0-10v	NO					
1126-LED	O2C	18	2420	0-10v	NO					
	O4C	36	4840	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 www.lightwayind.com • sales@lightwayind.com

