

VLXV-LED

Construction:

- Steel chassis and end caps
- Diffuser is white smooth acrylic or optional clear prismatic acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts to standard J-Box with slotted anchor holes
- Optional battery backup (36" or 48" only)
- Spring end caps for no visible fasteners
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



Type:	
Job Name:	



Length - 24" - 36" - 48" - 60" - 72"
 Height - 4 1/4"
 Depth - 4 1/4"



ORDERING INFORMATION

Example: VLXV-36-LED-O3C-2-W1-WSA

VLXV

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
24-LED	O2C	18	2420	0-10v	NO	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory
36-LED	O3C	27	3630	0-10v	NO	Optional 3 3500K		Optional (See Price List) M17 Brass Powder	Optional Lens Material (see Price List) CPA Clear Prismatic Acrylic	90CRI Consult Factory
48-LED	O4C	36	4840	0-10v	NO					Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minute



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

