

SSOW-LED

Construction:

- Steel housing and chassis
- Diffuser is white textured polycarbonate or optional white smooth polycarbonate
- Optional alabaster acrylic lenses

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Closed top eliminates upward light pollution
- Optional battery backup
- Optional photocell (option 21) – specify voltage
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

| | |
|-----------|--|
| Type: | |
| Job Name: | |



| | | |
|----------------|----------------|----------------|
| SSOW-12 | SSOW-15 | SSOW-22 |
| Height - 12" | Height - 13 ¾" | Height - 18 ½" |
| Width - 8" | Width - 10" | Width - 15" |
| Depth - 5 ¼" | Depth - 5 ½" | Depth - 7 ½" |



ORDERING INFORMATION

Example: **SSOW-22-LED-O2C-4-Z1-WTP**

SSOW

| Size | LED | | | | | Kelvin | Cage | Finish | Diffuser | Options | | |
|--------|-----|-------|---------------|-----------|-------------|----------------------------|--|----------------------------------|---|--|---|--|
| | | Watts | Source Lumens | Dimming | Energy Star | | | | | | | |
| 12-LED | F1H | 9 | 1400 | 0-10v | YES | 2 3000K 4 4000K | B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass | WTP White Textured Polycarbonate | DIM LED dimming driver (0 - 10v) DIMLED Line Voltage /TRIAC/ELV/120v See Resource Page 90CRI Consult factory ES Energy Star listed components 16 Bottom Lens | | | |
| | F1O | 10 | 863 | TRIAC/ELV | YES | Optional 3 3500K | | | | AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate | 21 Photocell - See Notes -01 120 volt -02 277 volt Optional Voltage -347V Input voltage to 347v | |
| | F1P | 15 | 1361 | TRIAC/ELV | YES | | | | | | | Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes |
| | F1J | 20 | 2820 | 0-10v | YES | | | | | | | |
| 15-LED | F1H | 9 | 1400 | 0-10v | YES | | | | | | | |
| | F1O | 10 | 863 | TRIAC/ELV | YES | | | | | | | |
| | O2B | 15 | 2000 | 0-10v | NO | | | | | | | |
| | F1P | 15 | 1361 | TRIAC/ELV | YES | | | | | | | |
| | F1J | 20 | 2820 | 0-10v | YES | | | | | | | |
| 22-LED | F1H | 9 | 1400 | 0-10v | YES | | | | | | | |
| | O2C | 18 | 2420 | 0-10v | NO | | | | | | | |
| | | | | | | | | | | | | |



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

