

SDWW-LED

Construction:

- Steel housing and chassis
- Diffuser is white textured or clear textured polycarbonate

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Optional photocell (21)
- Optional J-Box with knockouts for surface mount conduit - increases fixture depth to 4"
- ADA Compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



SDWW-7-LED

Height - 6 3/4"
 Width - 8 1/2"
 Depth - 2 1/4"



ORDERING INFORMATION

Example: SDWW-7-LED-01A-4-B1-WTP

SDWW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder	WTP White Textured Polycarbonate Optional Lens Material (See Price List) CTP Clear Textured Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components 90CRI Consult Factory 21 Photocell - See Notes -01 120 volt -02 277 volt 39 J-Box with Knockouts 42 All Aluminum Construction
7-LED	O1A	6	800	0-10v	NO	Optional 3 3500K				
	F1X	10	1087	TRIAC/ELV	YES					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

