

# RBSH-LED

## Construction:

- Steel housing and chassis
- Diffuser is .080" thick white smooth polycarbonate
- Optional alabaster acrylic is .080" thick

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Canopy mounts to J-Box with integral safety cable
- Custom mounting heights and cage designs available
- Optional battery backup
- Single stem 45-degree swivel standard
- Standard bottom lens is white smooth polycarbonate; optional clear acrylic lens or solid cover
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



Cage (A)

### RBSH-24

Height - 24 3/4"  
Width - 8 1/4"  
OAH - 44"

### RBSH-36

Height - 37"  
Width - 8 1/4"  
OAH - 54"



## ORDERING INFORMATION

Example: RBSH-24-LED-B-O16B-3-Z3-WSP-WBL-1SLM45-44"OAH

## RBSH

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options
24-LED	O8B	58	8000	0-10v	NO	2 3000K 4 4000K	A B	B1 Satin Black B2 Text Black Z1 Satin Bronze	WSP White Smooth Polycarbonate	(Suspension Systems) Please list Over All Height 1S45 - Single Stem (Standard) 1SLM45 - Single Stem 45 degree swivel 1S154AC - Single Stem w/Aircraft Cable
	O16B	116	16000	0-10v	NO	Optional 3 3500K	X	Z3 Text Bronze W1 Yolk White W2 Gloss White	Optional Lens Material (see Price List)	4AC - Aircraft Cable w/SJ cord WSJ - White "SJ" Cord BSJ - Black "SJ" Cord
								T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	Optional Bottom Lens (see Price List)
								Optional (See Price List) M17 Brass Powder	WBL White Bottom Lens	Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
36-LED	O8C	72	9680	0-10v	NO					
	O16C	143	19360	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
East Coast Sales: 866-350-0991 • fax 866-490-5754  
www.lightwayind.com • sales@lightwayind.com

