

PNBC-LED

Construction:

- Steel pan
- Diffuser is frosted smooth glass

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-Box installation
- Optional Battery Backup
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



PNBC-17

Height - 5 3/4"
Diameter 16 1/2"

PNBC-21

Height - 7 1/4"
Diameter 20 3/4"



ORDERING INFORMATION

Example: PNBC-21-LED-F1Q-4-T6-FSG

PNBC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
17-LED	F1L	9	1400	0-10v	YES	2 3000K 4 4000K Optional 3 3500	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass P7 Brushed Steel P9 Brushed Nickel	FSG Frosted Smooth Glass Optional Lens Material (see Price List) WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components 90CRI Consult Factory OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes	
	F1K	13	2115	0-10v	YES					
	O3B	22	3000	0-10v	NO					
	L1A	36	4000	0-10v	NO					
	F1P	15	1361	TRIAC/ELV	YES					
	F1Q	23	2057	TRIAC/ELV	YES					
21-LED	F1K	13	2115	0-10v	YES					
	L1A	36	4000	0-10v	NO					
	F1P	15	1361	TRIAC/ELV	YES					
	F1Q	23	2057	TRIAC/ELV	YES					



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

