

DKLW-LED

Construction:

- Steel housing, chassis and cage
- Shield design offset from lens
- Diffuser is .10" thick extruded white acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; keyhole slots left and right
- Top and bottom white acrylic lens- standard
- Optional photocell (21) increases fixture depth 1 ½"
- Optional battery backup (Excluding DKLW-10)
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Integral Power Supply
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



DKLW-10	DKLW-16	DKLW-22	DKLW-26
Height - 10"	Height - 16"	Height - 22 ¼"	Height - 26½"
Width - 9"	Width - 9"	Width - 9"	Width - 9"
Depth - 6"	Depth - 6"	Depth - 6"	Depth - 6"



ORDERING INFORMATION

Example: **DKLW-26-LED-O2C-4-B1-WSA-DIM**

DKLW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
10-LED	O2A	12	1600	0-10v	NO	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory
16-LED	O2C	18	2420	0-10v	NO	Optional 3 3500K				21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt
22-LED	O2B	15	2000	0-10v	NO					90CRI Consult Factory
	O3C	27	3630	0-10v	NO					42 All Aluminum Construction
	O4B	29	4000	0-10v	NO					Optional Voltage -347V Input voltage to 347v
26-LED	O2C	18	2420	0-10v	NO					Battery Backup Options (Available with 0-10v only) (Excludes DKLW-10)
	O4C	36	4840	0-10v	NO					BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

