

### Construction:

- Spun Aluminum Side cover
- Laser Etched Acrylic lens

### Light Source:

- LED
- Dimming to 10% **Included**

### Notes:

- Keyhole slots for standard J-box
- Down Light only
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80, Optional CR > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



- See RKTH for matching pendant

### RKTC-24

Height - 4.5"

Diameter - 24"



## ORDERING INFORMATION

Example: RKTC-24-LED-L1A-4-G3-WFA

### RKTC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
						2 3000K		B1 Satin Black	WFA White Frosted Acrylic	<b>DIM</b> LED dimming driver (0 - 10v) <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v Consult Factory  <b>OCCHFA</b> Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i>  Optional Voltage <b>-347V</b> Input voltage to 347v  <b>Battery Backup Options</b> <i>(Available with 0-10v only)</i> <b>BB10</b> 10 Watts (1170lm) for 90-Minute
					3 3500K		B2 Text Black			
24-LED	L1A	36	4000	0-10v	NO		G3 Dark Green			
24-LED	O8C	72	9680	0-10v	NO		R1 Red			
							U10 Bengal Blue			
							Z1 Satin Bronze			
							Z3 Text Bronze			
							W1 Yolk White			
							W2 Gloss White			
							T4 Shimmer Gray			
							M13 Anod Silver			
							T6 Pewter			
							W13 Pearl Beige			
							Optional (See Price List)			
							M17 Brass Powder			

