

BLSC-LED

Construction:

- Steel pan and fins
- Diffuser is white frosted acrylic lens designed for LED light source

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- Optional battery backup - Requires 1 3/4" extension ring
- Optional occupancy sensor
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



BLSC-14-LED

Width - 14"
 Height - 4 3/4"
 w/ext ring - 6 1/2"



ORDERING INFORMATION

Example: **BLSC-14-LED-F1O-4-W2-WFA**

BLSC

Size	LED					Kelvin	Cage	Finish	Diffusers	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 York White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WFA White Frosted Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
14-LED	F1H	9	1400	0-10v	YES	Optional 3 3500K	Optional (See Price List) M17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel			42 Aluminum Pan
	F1O	10	863	TRIAC/ELV	YES					90CRI Consult Factory
	F1P	15	1361	TRIAC/ELV	YES					OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet
	F1K	13	2115	0-10v	YES					Battery Backup Options (Requires 1 3/4" extension ring) (On Board Driver Engine only)
	F1Q	23	2057	TRIAC/ELV	YES					BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

