

PLBV-LED

Construction:

- Steel chassis
- Diffuser is clear white smooth acrylic with acrylic end caps

Light Source:

- LED
- Dimming to 10% included

Notes:

- Mounts to standard J-Box with slotted anchor holes
- ADA compliant
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	

**PLBV-24**

Height - 4 3/4"

PLBV-36

Height - 4 3/4 "

PLBV-48

Height - 4 3/4"

Depth - 4"

Depth - 4"

Depth - 4"

Length - 25 1/2"

Length - 37 1/2"

Length - 49 1/2"



ORDERING INFORMATION

Example: PLBV-36-LED-O3C-4-WM-WSA

PLBV

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		SW Solid White End-Caps	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory
24-LED	O2C	18	2420	0-10v	NO					
	F1Y	30	3235	TRIAC/ELV	YES					
36-LED	O3C	27	3630	0-10v	NO					
48-LED	O4C	36	4840	0-10v	NO					
60-LED	O5C	45	6050	0-10v	NO					
72-LED	O6C	54	7260	0-10v	NO					
										Battery Backup Options <i>(Available with 0-10v only)</i> BB10 10 Watts (1170lm) for 90-Minute



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286
www.lightwayind.com • sales@lightwayind.com



Revision: 04/10/2026