

RFXW-LED

Construction:

- Steel housing and chassis
- Front shield is steel or aluminum

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Universal mounting pattern – hardware included
- Up / Down light
- ADA compliant
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



RFXW-18

Height - 5"

Width - 18"

Depth - 4"



ORDERING INFORMATION

Example: RFXW-18-LED-F2D-4-Z1

RFXW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K				
18-LED	F2B	12	1180	0-10v	NO			B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel		DIM LED dimming driver (0 - 10v) RKS ON/OFF Rocker Switch Optional Voltage -347V Input voltage to 347v
	F2D	20	2192	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 800-325-4448 / 661-257-0286
www.lightwayind.com • sales@lightwayind.com



Revision: 02/03/2026