

# BPSH-LED

## Construction:

- Steel housing and chassis
- Diffuser is .080" thick white smooth or textured polycarbonate.
- Optional amber, beige or opal alabaster acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Mounts standard "J-Box", hardware included
- Standard is 3' of chain with 6' of cord
- Optional stem and swivel mounting – consult Factory
- Bottom of fixture is open; optional clear bottom lens or solid bottom cover (no down light)
- UL and CUL listed **DAMP** location
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



<b>BPSH-12</b>	<b>BPSH-16</b>	<b>BPSH-22</b>
Height - 12"	Height - 16"	Height - 22"
Width - 7 1/4"	Width - 8 1/2"	Width - 10"



## ORDERING INFORMATION

Example: **BPSH-16-LED-O4C-4-Z3-WSP-CFM-CBL**

### BPSH

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options
12-LED	O4B	29	4000	0-10v	NO	2 3000K 4 4000K  Optional 3 3500		B1 Satin Black	WTP White Textured Polycarbonate  WSP White Smooth polycarbonate  Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	<b>(Suspension Systems)</b> Please list <b>Over All Height</b> <b>CFM</b> Ceiling Flush Mount <b>1SLM45</b> -Single Stem 45 degree swivel <b>CHN</b> -___ - 3' of chain and 6' cord (STD) <b>WSJ</b> - White "SJ" Cord <b>BSJ</b> - Black "SJ" Cord  <b>DIM</b> LED dimming driver (0 - 10v) <b>90CRI</b> Consult Factory <b>CBL</b> Clear Bottom Lens <b>SSB</b> Solid Bottom Cover
	1E26		0	TRIAC/ELV	NO			W1 Yolk		
								W2 Gloss White		
16-LED	O4C	36	4840	0-10v	NO			W3 Text White		
	1E26		0	TRIAC/ELV	NO			W13 Pearl Beige		
								Z1 Satin Bronze		
22-LED	O8B	58	8000	0-10v	NO			Z3 Text Bronze		
	1E26		0	TRIAC/ELV	NO					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

