

CWSC-LED

Construction:

- Steel pan
- Diffuser is white smooth acrylic

Light Source:

- LED
- Dimming to 10% **included**

Notes:

- Keyhole slots for standard J-Box installation
- Optional aluminum pan
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



CWSC-12-LED

Height - 3 1/2"

Width - 12"

Depth - 12"



ORDERING INFORMATION

Example: CWSC-12-LED-F1P-4-W2-WSA

CWSC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		W2 Gloss White	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components T24 Title 24/JA8 Compliant (F10, F1P & F1Q configuration only) 90CRI Consult Factory 42 All Aluminum Construction OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet Optional Voltage -347V Input voltage to 347v
12-LED	F1L	9	1400	0-10v	YES	Optional 3 3500K				
	F1O	10	863	TRIAC/ELV	YES					
	F1P	15	1361	TRIAC/ELV	YES					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

