

REBH-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white smooth polycarbonate
- Optional alabaster acrylic (thickness varies by fixture size)

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Canopy mounts to ceiling J-Box with safety cable
- Custom mounting heights available
- Single stem 45-degree swivel standard
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



REBH-24	REBH-37
Height - 6"	Height - 6"
Width - 24"	Width - 37"
OAH - 24"	OAH - 24"



ORDERING INFORMATION

Example: REBH-24-LED-O6C-3-Z3-BAA-4S-24"OAH

REBH

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSP White Smooth Polycarbonate Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	(Suspension Systems) Please list Over All Height IS45 -Single Stem 45 degree swivel 4S Four Stem 1S154AC - Single Stem w/Aircraft Cable 4AC - Aircraft Cable w/SJ cord WSJ - White "SJ" Cord BSJ - Black "SJ" Cord DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) 90CRI Consult Factory Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minute
24-LED	O6C	54	7260	0-10v	NO	Optional 3 3500K		W11 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass	AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	
	O8C	72	9680	0-10v	NO					
37-LED	O8C	72	9680	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

