

# MENW-600-LED

## Construction:

- Steel housing and chassis
- Diffuser UV-stabilized, high impact resistant, 100% DR acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Integral mounting plate; keyhole slots
- Top and bottom white acrylic lens - standard
- Optional photocell (21) increases fixture depth 1 1/2"
- Optional battery backup
- Optional lens cover (NCL) prevents up/down light
- ADA compliant
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components
- You may also like the [MERW](#) or [MANW](#) Series

Type:	
Job Name:	



## DESIGN OPTIONS



**MENW-A**



**MENW-B**



**MENW-C**



**MENW-D**



**MENW-E**




**MENW-F**

### Fixture Overall Dimensions

- "H" - 12" - 16" - 18" - 26" - 38" - 50"
- "W" - 6 1/2"
- "D" - 4"
- "MC" - 6" - 8" - 9" - 13" - 19" - 25"

- See 900 or 1100 Series for other width options



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
[www.lightwayind.com](http://www.lightwayind.com) • [sales@lightwayind.com](mailto:sales@lightwayind.com)



# MENW-600-LED

## ORDERING INFORMATION

Example: MENW-616-LED-O1C-3-D-Z1-WSA

### MENW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
612-LED	F1H	9	1400	0-10v	YES	2 3000K 3 3500K 4 4000K	A	B1 Satin Black	WSA White Smooth Acrylic	<b>DIM</b> LED dimming driver (0 - 10v) <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v Consult Factory  <b>21</b> Photocell - Specify voltage 01 - 120 volt 02 - 277 volt <b>NCL</b> Aluminum Lens Cover - <i>See Notes</i> <b>ES</b> Energy Star listed components <b>T24</b> Title 24/JA8 Compliant (F1Y configuration only)  <b>39</b> J-Box with knockouts on all sides  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes
	F1P	15	1361	TRIAC/ELV	YES		B	B2 Text Black		
616-LED	O1C	9	1210	0-10v	NO		D	Z1 Satin Bronze		
618-LED	O2A	12	1600	0-10v	NO		C	Z3 Text Bronze		
626-LED	O2C	18	2420	0-10v	NO		E	W1 Yolk White		
626-LED	F1Y	30	3235	TRIAC/ELV	YES		F	W2 Gloss White		
638-LED	O3C	27	3630	0-10v	NO		X	W3 Text White		
650-LED	O4C29	29	3412	0-10v	NO			T4 Shimmer Gray		
	O4C	36	4840	0-10v	NO			M13 Anod Silver		
								T6 Pewter		
							W13 Pearl Beige			
							<b>Optional</b> (See Price List)			
							M17 Brass Powder			
							P2 Brushed Alum			
							P9 Brushed Nickel			



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com



Revision: 12/08/2022