




B1 Satin  
Black




B2 Textured  
Black



M13 Anodized  
Silver




T6 Pewter



W13 Pearl  
Beige




W1 Yolk White



Z1 Satin  
Bronze




Z3 Textured  
Bronze



T4 Shimmer  
Gray



W3 Textured  
White



W2 Gloss  
White



28435 Industry Drive., Valencia, California 91355  
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
[www.lightwayind.com](http://www.lightwayind.com) • [sales@lightwayind.com](mailto:sales@lightwayind.com)



# PODH-LED

## Construction:

- Steel chassis with lightweight aluminum rings
- Elliptical white smooth acrylic bowl is standard
- Optional alabaster bowl available

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Canopy mounts to J-Box with integral safety cable
- Custom mounting heights available with optional extension stem (AC-STEM)
- Standard 70% down light / 30% uplight - Custom options available
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



<b>PODH-30-LED</b>	<b>PODH-36-LED</b>	<b>PODH-48-LED</b>
Height - 7" EL	Height - 10" EL	Height - 11" EL
Width - 30"	Width - 36"	Width - 48"
OAH - 18"	OAH - 36"	OAH - 36"



## ORDERING INFORMATION

Example: **PODH-36-LED-O18C-4-Z1-WSA-1SAC-OAH-36**

### PODH

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige  <b>Optional</b> (See Price List) <b>M17</b> Brass Powder	<b>WSA</b> WhiteSmooth Acrylic  <b>Optional Lens Material</b> (see Price List)  <b>AHA</b> Amber Honey Alabaster <b>BAA</b> Beige Alabaster <b>OAA</b> Opal Alabaster	<b>(Suspension Systems)</b> Please list <b>Over All Height</b> <b>1SAC</b> - Single Stem with Aircraft Cable  <b>AC-STEM</b> - Extends over all height  <b>DIM</b> LED dimming driver (0 - 10v)  <b>OCCHFA</b> Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i>  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes
<b>30-LED</b>	<b>O9C</b>	80	10890	0-10v	NO					
<b>36-LED</b>	<b>O18C</b>	160	21780	0-10v	NO					
<b>48-LED</b>	<b>O20C</b>	178	24200	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 www.lightwayind.com • sales@lightwayind.com

