

BRAW-LED

Construction:

- Steel housing and chassis
- Seamless one piece .060" thick white smooth polycarbonate diffuser which includes the top and bottom

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- Top and bottom lens allows for up and down light
- Custom printed lens styles available
- ADA compliant
- Optional battery backup
- Optional Anti-Ligature Compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



Optional WHP Lens



BRAW-11

Height - 11"
Width - 8 1/4"
Depth - 3 1/2"

ORDERING INFORMATION

Example: **BRAW-11-LED-F1H-4-B1-WTP**

BRAW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
11-LED	F1H	9	1400	0-10v	YES	2 3000K 4 4000K		B1 Satin Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk W2 Gloss White W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSP White Smooth Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
	F1O	10	863	TRIAC/ELV	YES	Optional 3 3500K		Optional (See Price List)	Optional Lens Material (see Price List)	ES Energy Star listed components 90CRI Consult Factory
	F1P	15	1361	TRIAC/ELV	YES				WHP White Hexagon Polycarbonate	Optional Voltage -347V Input voltage to 347v
	O2A	12	1600	0-10v	NO				WXP Custom Polycarbonate	OCCHFB Concealed Occupancy Sensor (O2A Configuration Only) See Sensor Resource Sheet
	F1J	20	2820	0-10v	YES					Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

