

# BERW-LED

## Construction:

- Aluminum chassis
- Diffuser is injection molded white smooth acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Keyhole mounting
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

<b>Type:</b>	
<b>Job Name:</b>	



## BERW-10

Height - 9 1/2"  
 Width - 10"  
 Depth - 4"



## ORDERING INFORMATION

**Example: BERW-10-LED-F1P-3-P1-WSA**

## BERW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		M13 Anod Silver P0 Polished Brass* T4 Shimmer Gray T6 Pewter W1 Yolk W2 Gloss White W3 Text White W13 Pearl Beige	WSA White Smooth Acrylic	DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
10-LED	F1P	15	1361	TRIAC/ELV	YES	Optional 3 3500K		Optional (See Price List) P1 Chrome* P9 Brushed Nickel M16 Antique Brass		ES Energy Star listed components T24 Title 24/JA8 Compliant (F1P configuration only)
								* Interior Use Only		90CRI Consult Factory



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com



Revision: 05/21/2021