

ETOV-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white smooth acrylic
- Optional alabaster lenses are .080" thick acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts to standard J-Box with slotted anchor holes
- Perforated front panel (PP) reduces front lighting
- Solid top (ST) eliminates up light
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



Length - 18" - 24" - 36" - 48" - 60" - 72" - 96"

Height - 4½"

Depth - 3¼"



ORDERING INFORMATION

Example: ETOV-24-LED-O2C-4-Z3-WSA

ETOV

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder P2 Brushed Alum	WSA White Smooth Acrylic Optional Lens Material <i>Available with 18" - 48" only</i> (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) PP Perforated Front Panel ST Solid Top (No Up Light)
18-LED	O2A	12	1600	0-10v	NO					
24-LED	O2C	18	2420	0-10v	NO					
36-LED	O3C	27	3630	0-10v	NO					
48-LED	O4C	36	4840	0-10v	NO					
60-LED	O5C	45	6050	0-10v	NO					
72-LED	O6C	54	7260	0-10v	NO					
96-LED	O8C	72	9680	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 www.lightwayind.com • sales@lightwayind.com

