

EBDW-LED

Construction:

- Steel housing and chassis
- Diffuser is .060" thick white textured polycarbonate
- Optional alabaster lenses are .080" thick acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Open top and bottom for up and down light
- Optional Battery Backup
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



EBDW-14

Height - 14"
Width - 10"
Depth - 4"

EBDW-16

Height - 15 1/2"
Width - 14"
Depth - 4"



ORDERING INFORMATION

Example: **EBDW-14-LED-F10-4-Z1-WTP**

EBDW

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options	
14-LED	F1H	9	1400	0-10v	YES	2 3000K 4 4000K		B1 Satin Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W2 Gloss White W1 Yolk White Z1 Satin Bronze Z3 Text Bronze	WTP White Textured Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components 90CRI Consult Factory Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes	
	F10	10	1065	TRIAC/ELV	YES	Optional 3 3500K		Optional Finishes (see Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass	Optional Lens Material (see Price List)		
	F1P	15	1724	TRIAC/ELV	YES				AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster		
16-LED	F1H	9	1400	0-10v	YES						
	F1P	15	1724	TRIAC/ELV	YES						
	O2C	18	2420	0-10v	NO						



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

