

SAPP-LED

Construction:

- Steel housing and chassis
- Diffuser is white textured polycarbonate
- Optional alabaster acrylic lenses

Light Source:

- LED

Notes:

- Mounts to 3" round pole – fitter included
- Fixture dimensions excluded fitter
- See supplemental spec sheet on website for pole options
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



SAPP-15-LED

Height - 15"
Width - 8 1/4"
Depth - 8 1/4"

SAPP-22

Height - 22"
Width - 12"
Depth - 12"



ORDERING INFORMATION

Example: SAPP-15-LED-O4B-4-Z1-WTP

SAPP

Size	LED					Kelvin	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star				
15-LED	1E26		0	TRIAC/ELV	NO	2 3000K 4 4000K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass	WTP White Textured Polycarbonate Optional Lens Material (See Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	Optional Voltage -347V Input voltage to 347v Pole Options (see supplemental spec sheet on website and price list)
	O4B	29	4000	0-10v	NO	Optional 3 3500K			
	O4C	36	4840	0-10v	NO				
22-LED	O4C	36	4840	0-10v	NO				
	O8C	72	9680	0-10v	NO				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

