

CJRC-LED

Construction:

- Injection molded polycarbonate housing and lens

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Knockouts for standard "J-Box" mounting or conduit drill points for surface mounted conduit
- Vandal resistant polycarbonate
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



CJRC-11-LED

Height - 3.94"

Diameter - 11.87"



ORDERING INFORMATION

Example: CJRC-11-LED-O2A-4-B99-WSP

CJRC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
12-LED	O2A	12	1600	0-10v	NO	2 3000K 3 3500K 4 4000K		B99 Black	WFP White Frosted Polycarbonate	DIM LED dimming driver (0 - 10v)
	O3A	14	2240	0-10v	NO			Optional Finishes (see Price List)		21 Photocell - See Notes -01 120 volt -02 277 volt
	O4A	18	2880	0-10v	NO			W99 White		



28435 Industry Drive., Valencia, California 91355
 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 www.lightwayind.com • sales@lightwayind.com

