

VLCV-LED

Construction:

- Steel chassis
- Diffuser is injection molded white smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts to standard J-Box with slotted anchor holes
- Optional battery backup
- Vertical or Horizontal mounting
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



VLCV-24

Height - 6"
Depth - 4 1/2"
Length - 27"

VLCV-36

Height - 6"
Depth - 4 1/2"
Length - 39"

VLCV-48

Height - 6"
Depth - 4 1/2"
Length - 51"



ORDERING INFORMATION

Example: VLCV-36-LED-03C-4-W2-WSA

VLCV

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		W2 Gloss White	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory 90CRI Consult Factory Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minute
24-LED	02C	18	2420	0-10v	NO	Optional 3 3500K				
36-LED	03C	27	3630	0-10v	NO					
48-LED	04C	36	4840	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

