

# MRRW-LED

## Construction:

- Steel housing and chassis
- Diffuser UV-stabilized, high impact resistant, DR acrylic
- Top and bottom white acrylic lens - standard
- Accent rings are steel tubing

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Keyhole slots left and right
- Top and bottom white acrylic lens - standard
- Optional photocell (21) increases fixture depth 1 1/2"
- Optional lens cover (ALC) eliminates up/down light
- Optional battery backup
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



Height - 16"  
 Width - 9"  
 Depth - 5 1/2"  
 MC - 8"



## ORDERING INFORMATION

Example: MRRW-916-LED-P-O2C-4-Z3-WSA

### MRRW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
916-LED	O2C	18	2420	0-10v	NO	2 3000K 3 3500K 4 4000K I	P X	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 York White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige  Optional (See Price List) M17 Brass Powder	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v)  21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt  42 All Aluminum Construction  ALC Aluminum Lens Cover - See Notes 39 J-Box with knockouts on all sides  Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

