

NBCW-LED

Construction:

- Steel housing and chassis
- Diffuser UV-stabilized, high impact resistant, 100% DR acrylic
- Center accent bar and rings are extruded aluminum

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup - hardware included
- Open top and bottom
- Horizontal or vertical mounting
- Optional battery backup
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components
- **For WET listed version see MANW Series**

Type:	
Job Name:	



NBCW-16-LED

Height - 16"
Width - 7 1/4"
Depth - 4 1/4"

NBCW-24-LED

Height - 24"
Width - 7 1/4"
Depth - 4 1/4"



ORDERING INFORMATION

Example: NBCW-16-LED-O2C-4-T6-WSA

NBCW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
16-LED	O2C	18	2420	0-10v	NO	2 3000K 3 3500K 4 4000K		B1 Satin Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W2 Gloss White W1 Yolk White Z1 Satin Bronze Z3 Text Bronze Optional Finishes (see Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
24-LED	O2C	18	2420	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

