

NEBW-LED

Construction:

- Housing and chassis is steel
- Diffuser is vandal resistant acrylic


Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; Hardware include
- Mounts on a 2x4 jbox or 4" square post
- Optional battery backup available on fixtures 426 & larger
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



	DIM 'A'	Mount-Center
NEBW-413	13"	6.5"
NEBW-426	26"	13"
NEBW-438	38"	19"
NEBW-450	50"	25"
NEBW-460	60"	30"



ORDERING INFORMATION

Example: NEBW-426-LED-O2C-3-B1-B1

NEBW

Size	LED					Kelvin	Cage	Finish	Front Deco Finish	Options
		Watts	Source Lumens	Dimming	Energy Star					
413-LED	O1C	9	1210	0-10v	NO	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) 42 All Aluminum Construction Battery Backup Options Available (426 & Larger) BB10 Battery backup unit providing 10 Watts (1170lm) for 90-Minute
426-LED	O2C	18	2420	0-10v	NO			Optional (See Price List) M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel	Optional (See Price List) M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel	
438-LED	O3C	27	3630	0-10v	NO					
450-LED	O4C	36	4840	0-10v	NO					
460-LED	O5C	45	6050	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

