

BPSP-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white smooth or textured polycarbonate.
- Optional amber, beige or opal alabaster acrylic

Light Source:

- LED

Notes:

- Mounts to 3" round pole – aluminum fitter included
- Fixture dimensions exclude fitter
- Wall mount bracket option
- See supplemental spec sheet on website for pole options
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



BPSP-12

Height - 12"
Width - 7 1/4"

BPSP-16

Height - 16"
Width - 8 1/2"

BPSP-22

Height - 22"
Width - 10"



ORDERING INFORMATION

Example: **BPSP-16-LED-O4C-4-Z3-WSP**

BPSP

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W1 Yolk W2 Gloss White W3 Text White W13 Pearl Beige Z1 Satin Bronze Z3 Text Bronze	WTP White Textured Polycarbonate WSP White Smooth polycarbonate Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	27 Wall Mount Bracket Pole Options (see supplemental spec sheet on website and price list)
12-LED	O4B	29	4000	0-10v	NO					
	1E26		0	TRIAC/ELV	NO					
16-LED	O4C	36	4840	0-10v	NO					
	1E26		0	TRIAC/ELV	NO					
22-LED	O8B	58	8000	0-10v	NO					
	1E26		0	TRIAC/ELV	NO					



28435 Industry Drive., Valencia, California 91355
800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
www.lightwayind.com • sales@lightwayind.com

