

RERC-LED

Construction:

- Steel housing and chassis
- Diffuser is white smooth acrylic
- Optional alabaster acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-Box – hardware included
- UL and CUL listed **DAMP** location
- Optional battery backup - increases depth by 1 1/2"
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



RERC-18
Height - 6"
Diameter - 18"

RERC-24
Height - 6"
Diameter - 24.75"

RERC-30
Height - 8"
Diameter - 30"

RERC-36
Height - 8"
Diameter - 36"



ORDERING INFORMATION

Example: RERC-24-LED-02C-4-Z3-WSA

RERC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
						2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory 90CRI Consult Factory OCCHFA Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i>
18-LED	O2C	18	2420	0-10v	NO	Optional 3 3500K		Optional (See Price List) M17 Brass Powder		Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
24-LED	4E26		0	TRIAC/ELV	NO					
	O2C	18	2420	0-10v	NO					
	L1A	36	4000	0-10v	NO					
30-LED	L1A	36	4000	0-10v	NO					
36-LED	O6C	54	7260	0-10v	NO					
	O8C	72	9680	0-10v	NO					
	O9C	80	10890	0-10v	NO					
	O12C	107	14520	0-10v	NO					
	O16C	143	19360	0-10v	NO					
	O18C	160	21780	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

