

MNTW-WET-LED

Construction:

- Steel housing and chassis
- Diffuser is white textured polycarbonate

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included (MNTW-14)
- Bi-directional keyhole slots (MNTW-16)
- Optional Battery Backup
- Optional Photocell
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



MNTW-14-WET

Height - 13 ¾"
Width - 10 ½"
Depth - 5"

MNTW-16-WET

Height - 16"
Width - 11 ½"
Depth - 7 ⅛"



ORDERING INFORMATION

Example: MNTW-14-WET-LED-F1D-4-P2-WTP

MNTW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
14-LED	F1O	10	863	TRIAC/ELV	YES	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTP White Textured Polycarbonate Optional Lens Material (See Price List) BSA Blue Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page T24 Title 24/JA8 Compliant (F10 configuration only) ES Energy Star listed components 42 All Aluminum Construction 21 Photocell - See Notes -01 120 volt -02 277 volt Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
	F1D	12	1230	0-10v	NO			Optional (See Price List) M17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel		
	F2D	24	2460	0-10v	NO					
16-LED	O1A	6	800	0-10v	NO					
	O2A	12	1600	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

