

WMXV-LED

Construction:

- Steel housing and chassis
- Diffuser is extruded clear fluted acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts to standard J-Box with slotted anchor holes
- Optional battery backup
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Length - 16" - 24" - 36" - 48" - 72" - 96"

Height - 5 3/8"

Depth - 5"

Type:	
Job Name:	



ORDERING INFORMATION

Example: WMXV-36-LED-O3C-4-PO-CUA

WMXV

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	CUA Clear Fluted Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory
16-LED	O2A	12	1600	0-10v	NO	Optional 3 3500K				90CRI Consult Factory
24-LED	O2C	18	2420	0-10v	NO					
36-LED	O3C	27	3630	0-10v	NO					
48-LED	O4C	36	4840	0-10v	NO					
72-LED	O6C	54	7260	0-10v	NO					
96-LED	O8C	72	9680	0-10v	NO					
							Optional (see Price List) P0 Polished Brass P1 Chrome P9 Brushed Nickel M16 Antique Brass			Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minute



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

