

# BDYW-LED

## Construction:

- Cast aluminum housing
- Aluminum reflector
- Clear tempered glass lens

## Lamps:

- Lamps **INCLUDED**

## Notes:

- Wall mounting bracket attaches to 4" recessed outlet box
- Optional Photocell
- Optional Battery backup
- Dark Sky compliant
- UL and CUL listed WET location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



## BDYW-7

Height - 9 1/8"  
 Width - 18 1/8"  
 Depth - 9 1/8"



## ORDERING INFORMATION

Example: **BDYW-7-LED-O2C-2-Z99-CEG**

## BDYW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		<b>B1</b> Satin Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk <b>W2</b> Gloss White <b>W3</b> Text White <b>B2</b> Text Black <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige	<b>CEG</b> Clear Tempered Glass	<b>DIM</b> LED dimming driver (0 - 10v)  <b>21</b> Photocell - <i>See Notes</i> -01 120 volt -02 277 volt  <b>90CRI</b> Consult Factory  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutess
<b>7-LED</b>	<b>O2C</b>	18	2420	0-10v	NO	<b>Optional</b> 3 3500K				



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

